

Custom Control Properties

Property Name: dialogID

Required: true

Description: A Unique Value for the dialog, no spaces or special characters allowed.

example: Dialog1

Property Name: dataset

Required: true

Description: Select a view from the datasource list. You will need a unique datasource view for each picklist on the page even if it uses the same view. If you do not have anything listed, go to Xpage Properties, then Data , and add a view.

example: view1

Property Name: rowsPerPage

Default Value: 10

Description: How many entries do you want to show before the user will have to use the pager to go to the next page.

example: 11

Property Name: viewColumn

Description: The number of the column in the view, starting with 0
You can add as many columns as you would like to display from the view.

example: 1

Property Name: selectColumn

Required: false

Description: The number of the column you would like the value to be selected from. Column values start with 0. So the first column is 0, the second is 1.

example: 2

Property Name: fieldName

Description: The name of the field you would like the value to be selected from the document in

the view.

example: city

Property Name: buttonText

Default Value: ...

Required: false

Description: Text for the select button in the view picklist.

example: Select

Property Name: buttonImage

Description: Image for the select button in the view picklist.

example: ./add.png

Property Name: buttonClass

Description: The class for the select button in the view picklist.

example: button

Property Name: tableClass

Description: The class of the view picklist panel.

Property Name: headerClass

Description: The class for the headers on the view picklist.

Property Name: rowClass

Description: The class for the rows on the viewpicklist.

example: even, odd

Property Name: searchBar

Default Value: false

Description: Show or hide the Search Bar in the picklist.

Property Name: searchButtonText

Default Value: Search

Description: The text on the search button on the view picklist.

Property Name: searchButtonImage

Description: The image on the search button on the view picklist.

Property Name: searchButtonClass

Required: false

Description: The class of the search button on the view picklist.

Property Name: searchBarClass

Description: The class of the cell the search bar and pager sit in.

Property Name: pagerStyleFirst

Description: The 'First' button on the pager

Property Name: pagerStylePrevious

Description: The 'Previous' button on the pager

Property Name: pagerStyleCurrent

Description: The 'Current' button on the pager

Property Name: pagerStyleNext

Description: The 'Next' button on the pager

Property Name: pagerStyleLast

Description: The 'Last' button on the pager

Property Name: searchVar

Description: The global variable that the search filter uses on the view data source.

example: sessionScope.searchThis

Property Name: dialogHeight

Description: The height of the dialog box.

example: 100px

example2: 100%

Property Name: dialogWidth

Description: The width of the dialog.

example: 100px

example2: 100%

Property Name: dialogTitle

Description: The title of the view picklist

example: Please choose the correct value.

Property Name: typeAheadBar

Default Value: false

Description: Show or hide the type ahead filter on the view picklist.

Property Name: typeAheadVar

Description: The global variable that is used in the filter column on the view datasource.

example: sessionScope.typeahead1

Property Name: select

Default Value: Column

Description: What is selected when they press the view picklist select button. A column in the view, or a field on the document in the view.

Property Name: selectField

Description: The field name in the document you want to return as your selected value.

example: city

Property Name: onReturn

Default Value: Set Field Value

Required: true

Description: Set field value: will set the id of the element you want the selection to go into.

example: inputText1

Set Scope Value: Set a scope variable with a the value.

example: sessionScope.city

Set Document Value: set the value of a bound document datasource field.

example: document1.city

Property Name: varName

Description: The variable for Set Scope or set Document Value, depending on what is chosen.

example: document1.city

example2: sessionScope.city

Property Name: refreshID

Required: true

Description: The id of the element to refresh after your selection.

example: inputText1

Property Name: bottomBarClass

Description: The class of the bottom button bar.

Property Name: cancelButtonText

Default Value: Cancel

Description: The text on the cancel button.

example: Cancel

Property Name: cancelButtonClass

Description: The class of the cancel button.

Property Name: cancelButtonImg

Description: The image on the cancel button.

example: ./cancel.png

Property Name: type

Default Value: Single Value

Required: true

Description: Will this be a single value picklist or a multi-value picklist?

Property Name: finishButtonText

Default Value: Finish

Description: The Text on the finish button.

example: Finished

Property Name: finishButtonClass

Description: the class of the finish button.

Property Name: finishButtonImg

Description: The image on the finish button.

example: ./finish.png

Property Name: multiSelectButtonAddImg

Description: The image shown for adding a value on a multiselect picklist.

example: ./add.png

Property Name: multiSelectButtonRemoveImg

Description: The image shown for removing a value on a multiselect picklist.

example: ./delete.png

Property Name: multiSelectButtonClass

Description: The class of the add/remove button on a multi-value picklist.

Property Name: multiSelectButtonRemoveText

Description: The text on the select button a multi-value picklist to remove a value.

example: Remove

Property Name: multiSelectButtonAddText

Description: The text on the select button a multi-value picklist to add the value.

example: Add

Property Name: picklistButtonText

Description: The text on the button on the main Xpage to open the picklist dialog.

example: Choose your values

Property Name: picklistButtonClass

Description: The class on the button on the main Xpage to open the picklist dialog.

Property Name: picklistButtonImg

Description: The image on the button on the main Xpage to open the picklist dialog.

example: ./add.png
